

Model 5510S Panic-Rated Rim Exit Device - For wide stile and flush doors use
Model 5510F Fire-Rated Rim Exit Device - For wide stile fire labeled doors use



Application

- For use on single doors or double doors with mullion (fire rated device must use on 4' x 8' single or 8' x 8' double fire labeled doors).
- Fits for 1 3/4" (44mm) thick standard RHR or LHR hollow metal doors & wood doors, other than standard 1 3/4" is available but specify door thickness when ordered.
- Minimum Stile Width: 3 1/2" (90mm)

531 Strike Shim

Furnished with 532 Strike together. This shim is 1/8" thick for prepared doors with 1/2" stop, it is used to obtain correct distance between the device latch and the surface applied strike when the stop is 1/2" high. If the frame has 5/8" stop, then this shim is unnecessary. Steel, plated.

532 Panic Rim Strike

Surface applied. Standard on 5000 Series panic rim exit devices. Stainless steel, with a plated roller.

533 Fire Rim Strike

Surface applied. Standard on 5000 Series fire rim devices. It is 100% stainless steel including a roller.

Specifications

Device Head Cover-----	Stainless steel, nonferrous alloy
Chassis-----	Steel, plated
Mechanism Housing-----	Steel, or stainless steel
Push Bar-----	Steel, or stainless steel
End Cap-----	Steel, or stainless steel
Latch Bolt-----	100% stainless steel, deadlocking type, 11/16" (17mm) throw
Deadlocking Latch-----	100% Stainless steel, 5/8" (16mm) throw
Strike-----	531 & 532 Rim (panic rated) 533 Rim (fire rated)
Hand-----	Non-handed
Mounting Fasteners-----	Machine screws furnished standard, Sex Nut and Bolt (SNB) are required to use for wood doors. Order SNB separately.
Dogging*-----	Hex key dogging standard (Allen-type key furnished)
Dogging Options-----	Cylinder dogging or Less dogging
Finish-----	605, 630, 689, 690, four finishes
Dimensions-----	See Dimensions page
Device Length-----	See Device Length page
UL Listed-----	For Panic Hardware (Original listed model no.: 500SA) For Fire Exit Hardware (Original listed model no.: 5210AF)

* Fire rated rim device has no mechanical dogging. (Dogging device is not permitted on fire-rated exit device.)